

METHOD FOR LOCALLY FORMING DIFFERENT BAND GAP IN QUANTUM WELL BY DIELECTRIC-SEMICONDUCTOR COMPOSITE COVER LAYER

Publication number: KR20010036949 (A)

Publication date: 2001-05-07

Inventor(s): CHOI WON JUN [KR]; HAN IL GI [KR]; KANG GWANG NAM [KR]; KIM HOE JONG [KR]; KIM SEON HO [KR]; LEE HUI TAEK [KR]; LEE SEOK [KR]; WOO DEOK HA [KR] +

Applicant(s): KOREA INST SCIENCE TECHNOLOGY [KR] +

Classification:

- **international:** *H01L21/18; H01L21/02*; (IPC1-7): H01L21/18

- **European:**

Application number: KR19990044158 19991012

Priority number(s): KR19990044158 19991012

Abstract of KR 20010036949 (A)

PURPOSE: A method for locally forming a different band gap in a quantum well by a dielectric-semiconductor composite cover layer is provided to regulate a degree of disorder of the quantum well. **CONSTITUTION:** The method begins with growing an InGaAs/InGaAsP quantum well substrate by a chemical beam epitaxy technique. Next, a dielectric thin layer made of such as SiO₂ or SiN_x is formed as a cover layer on the quantum well substrate by a plasma-enhanced chemical deposition technique. After a heat treatment step is carried out at a temperature of 600 - 800[deg.]C for 4 - 16 minutes, the dielectric thin layer is removed. In addition, InP, InGaAs or InGaAsP is used as a semiconductor cover layer.

.....
Data supplied from the *espacenet* database — Worldwide